



## Building Installation Connector System AC 166®


G

Panel Mounting

### AC 166 GEKBU/ 3 WS

#### Order Info

reference number (ref. no.)	168453
PU	200
EAN	4028012112753



#### Type

connection type	push-in
number of poles	3 pole
coding	1 (mains)
colour	white
protection against incorrect plugging	yes
PE-function	yes

#### Electrical Data

rated voltage	250 V
rated current	20 A
rated impulse voltage	4.0 kV

#### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	14 AWG
clamping range	0.5 - 2.5 mm <sup>2</sup>
type of conductor	solid
stripping length	8.0 - 9.0 mm
fixing	catch wing
clamping units per pole	2
pole marking	L1 ⊕ N
wall thickness	1.3 - 2.5 mm

#### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	70 °C
T <sub>max</sub> component (operation)	100 °C
IP Code acc. to EN 60529	IP20
IP Code when plugged	IP40

## Materials

<b>insulator material</b>	PA
<b>contact material</b>	spring steel, brass
<b>flammability rating acc. to UL 94</b>	V-2

## Approvals

<b>acc. to EN 61535</b>	yes
<b>acc. to UL</b>	yes