



Building Installation Connector System AC 166®  
G  
Plug and Socket Connectors Flat Version  
AC 166 GBUF/315 PB ZEL WS



### Order Info

reference number (ref. no.)	17710
PU	200
EAN	4028012135431

### Type

Type	socket
connection type	screw
number of poles	3 pole
coding	5 (DALI)
colour	pastel blue white
protection against incorrect plugging	yes
strain relief	yes

### Electrical Data

rated voltage	250 V
rated current	20 A
rated impulse voltage	4.0 kV

### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	14 AWG
clamping range	0.5 - 4.0 mm <sup>2</sup>
sheathing cable diameter	7.5 - 8.5 mm
type of conductor	fine stranded, stranded, solid
stripping length	7.0 mm
dismantling length	32.0 mm
clamping units per pole	1
contact screw assembly	0.5 x 3.0 / ⌀ 0.3 Nm
strain relief assembly	PZ 1 / ⌀ 0.5 Nm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	70 °C
T <sub>max</sub> component (operation)	110 °C

<b>T<sub>min</sub> component (operation)</b>	-20 °C
<b>IP Code acc. to EN 60529</b>	IP20
<b>IP Code when plugged</b>	IP40

## Materials

<b>insulator material</b>	PA
<b>contact material</b>	brass
<b>flammability rating acc. to UL 94</b>	V-2

## Approvals

<b>acc. to EN 61535</b>	yes
<b>acc. to UL</b>	yes
<b>acc. to CSA</b>	yes

## Accessories

<b>AC 166 VSF SW</b>	169563
<b>AC 166 VSF WS</b>	169553