



Circular Connectors IP68  
Circular Connectors AC 169 kompakt  
**AC 169 REBU/4-3 M25**



### Order Info

reference number (ref. no.)	18899
PU	200
EAN	4028012133062

### Type

Type	panel mount socket
connection type	screw
number of poles	3 pole
colour	black
protection against incorrect plugging	yes
PE-function	yes

### Electrical Data

rated voltage	450 V
rated current	17.5 A
rated impulse voltage	4.0 kV

### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	14 AWG
clamping range	0.5 - 4.0 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
stripping length	6.0 mm
clamping units per pole	1
contact screw assembly	0.5 x 3.0 / ⌀ 0.5 Nm
housing hole	M25
wall thickness	1.0 - 7.0 mm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>max</sub> component (operation)	125 °C
T <sub>min</sub> component (operation)	-40 °C
IP Code acc. to EN 60529	IP68

## Materials

<b>insulator material</b>	PA
<b>contact material</b>	brass
<b>flammability rating acc. to UL 94</b>	V-2

## Approvals

<b>acc. to EN 61984</b>	yes
-------------------------	-----

## Accessories

<b>AC 169 RVKB M25</b>	729164
<b>AC 169 RWZ/2-4</b>	749964