



Circular Terminal Blocks IP68
Circular Terminal Blocks AC 180 basic

AC 180 SKG-I D24

Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 19077 |
| PU | 200 |
| EAN | 4028012122912 |



Type

| | |
|--------|-----------|
| Type | I-housing |
| colour | black |

Connection Data

| | |
|--------------------------|---------------|
| sheathing cable diameter | 7.0 - 13.5 mm |
|--------------------------|---------------|

Ambient Conditions

| | |
|---|--------|
| T _{max} ambient air (at rated current) | 125 °C |
| T _{max} component (operation) | 125 °C |
| T _{min} component (operation) | -40 °C |
| IP Code acc. to EN 60529 | IP68 |

Materials

| | |
|-----------------------------------|-----|
| insulator material | PA |
| flammability rating acc. to UL 94 | V-2 |

Approvals

Accessories

| | |
|--------------------|--------|
| AC 180 SK/ 2 SL | 19057 |
| AC 180 SK/ 3 SL | 19066 |
| AC 180 SK/ 3+3 SL | 19058 |
| AC 180 SK/ 4 SL | 19069 |
| AC 180 SK/ 5 SL | 19074 |
| AC 180 SK/ 6 SL | 19076 |
| AC 169 WKZ SW21/24 | 749960 |
| DR 16 RH | 729011 |
| DR 16 GS | 729032 |

| | |
|---------------------|--------|
| DR 16 1x14,0 | 729031 |
| DR 16 1x4,0 | 729033 |
| DR 16 1x6,5 | 729034 |
| DR 16 2x4,0 | 729035 |
| DR 16 2x5,5 | 729036 |
| DR 16 3x4,0 | 729037 |
| DR 16 4x3,5 | 729038 |
| DR 16 5x3,5 | 729009 |