



## Fused Terminal Blocks

### 503 SI/ 2 MDS GW

#### Order Info

reference number (ref. no.)	19935
PU	300
EAN	4028012137534



#### Type

Type	screw terminal block with fuse holder 5x20
connection type	screw
number of poles	2 pole
colour	naturalal
centre stop	yes

#### Electrical Data

rated voltage	400 V
rated current	10 A

#### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	22-12 AWG
clamping range	0.5 - 5.5 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
type of conductor internal	fine stranded, stranded, solid
type of conductor external	fine stranded, stranded, solid
stripping length	7.0 - 7.5 mm
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\cup$ 0.5 Nm
mounting hole diameter	3.1 mm
socket diameter	2.75 mm

#### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>min</sub> ambient air (operation)	-40 °C

#### Materials

insulator material	PA GW
contact material	brass

<b>flammability rating acc. to UL 94</b>	V-2
--	-----

---

## Approvals

---

<b>acc. to EN 60127</b>	yes
-------------------------	-----

---

<b>acc. to UL</b>	yes
-------------------	-----

---

## Accessories

---

<b>ZEL 110</b>	196420
----------------	--------

---

<b>ABK 503/ 2 GW</b>	193812
----------------------	--------

---