



Circular Terminal Blocks IP68
Circular Terminal Blocks AC 179 kompakt
AC 179 SKE/ 5 SL L M20



Order Info

reference number (ref. no.)	25860
PU	200

Type

Type	panel mount terminal block
connection type	screw
number of poles	5 pole
colour	black
centre stop	yes
strain relief	yes

Electrical Data

rated voltage	450 V
rated current	17.5 A

Connection Data

clamping range	0.25 - 1.5 mm ²
sheathing cable diameter	7.0 - 13.5 mm
type of conductor	fine stranded, stranded, solid
stripping length	6.0 mm
dismantling length	25.0 mm
clamping units per pole	1
lock nut assembly	1.5 Nm
grommet assembly	2.0 Nm
contact screw assembly	M2 - max. \curvearrowright 0.2 Nm
housing hole	M20
pole marking	1-2-3-4-5
wall thickness	1.0 - 9.0 mm
strain relief assembly	\curvearrowright 2.5 Nm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{max} component (operation)	125 °C
T _{min} component (operation)	-40 °C

IP Code acc. to EN 60529

IP68/IP69

Materials

insulator material

PA

contact material

brass

flammability rating acc. to UL 94

V-0

Approvals

acc. to EN 60998

yes

Accessories

AC 179 RVK/ 4 M20

749564

AC 173 BC SW

26280

DR 16 1x14,0

729031

DR 16 1x4,0

729033

DR 16 1x6,5

729034

DR 16 2x4,0

729035

DR 16 2x5,5

729036

DR 16 3x4,0

729037

DR 16 4x3,5

729038

DR 16 5x3,5

729009

DR 16 RH

729011

DR 16 GS

729032