



Circular Connectors IP68
Circular Connectors AC 173 click

AC 173 RST/5



Order Info

reference number (ref. no.)	26014
PU	200
EAN	4028012174225

Type

Type	plug
connection type	screw
number of poles	5 pole
colour	black
protection against incorrect plugging	yes

Electrical Data

rated voltage	500 V
rated current	17.5 A
rated impulse voltage	2.5 kV

Connection Data

clamping range	0.25 - 1.5 mm ²
sheathing cable diameter	7.0 - 13.0 mm
stripping length	6.0 mm
dismantling length	25.0 mm
clamping units per pole	1
contact screw assembly	M2 - max. \curvearrowright 0.2 Nm
pole marking	1-2-3/L-N-E
strain relief assembly	\curvearrowright 2.5 Nm

Ambient Conditions

T _{max} ambient air (at rated current)	60 °C
T _{max} component (operation)	125 °C
T _{min} component (operation)	-40 °C
IP Code acc. to EN 60529	IP66/IP68/IP69

Materials

insulator material	PA 6.6
--------------------	--------

contact material	brass
-------------------------	-------

flammability rating acc. to UL 94	V-0
--	-----

Approvals

acc. to EN 61984	yes
-------------------------	-----

Accessories

AC 173 BC SW	26280
---------------------	-------

AC 169 WKZ SW21/24	749960
---------------------------	--------

AC 173 RWZ/5	26060
---------------------	-------

AC 173 RVKS	26033
--------------------	-------

DR 16 RH	729011
-----------------	--------

DR 16 GS	729032
-----------------	--------

DR 16 1x14,0	729031
---------------------	--------

DR 16 1x4,0	729033
--------------------	--------

DR 16 1x6,5	729034
--------------------	--------

DR 16 2x4,0	729035
--------------------	--------

DR 16 2x5,5	729036
--------------------	--------

DR 16 3x4,0	729037
--------------------	--------

DR 16 4x3,5	729038
--------------------	--------

DR 16 5x3,5	729009
--------------------	--------