



Circular Connectors IP68
Circular Connectors AC 173 click
AC 173 REST/5 M20



Order Info

reference number (ref. no.)	26018
PU	200
EAN	4028012174263

Type

Type	panel mount plug
connection type	screw
number of poles	5 pole
colour	black
protection against incorrect plugging	yes

Electrical Data

rated voltage	500 V
rated current	17.5 A
rated impulse voltage	2.5 kV

Connection Data

clamping range	0.25 - 1.5 mm ²
stripping length	6.0 mm
dismantling length	25.0 mm
clamping units per pole	1
lock nut assembly	1.5 Nm
contact screw assembly	M2 - max. \curvearrowright 0.2 Nm
housing hole	M20
pole marking	1-2-3/L-N-E
wall thickness	- 3.0 mm

Ambient Conditions

T _{max} ambient air (at rated current)	60 °C
T _{max} component (operation)	125 °C
T _{min} component (operation)	-40 °C
IP Code acc. to EN 60529	IP66/IP68/IP69

Materials

insulator material	PA 6.6
contact material	brass
flammability rating acc. to UL 94	V-0

Approvals

acc. to EN 61984	yes
-------------------------	-----

Accessories

AC 173 RWZ/5	26060
AC 173 RVKS	26033