



Circular Terminal Blocks IP68  
Circular Terminal Blocks AC 179 kompakt  
**AC 179 SK/ 4-2 SL L**



### Order Info

reference number (ref. no.)	26754
PU	200

### Type

Type	Terminal Block
connection type	screw
number of poles	2 pole
colour	black
centre stop	yes
strain relief	yes

### Electrical Data

rated voltage	450 V
rated current	32 A

### Connection Data

clamping range	0.5 - 4.0 mm <sup>2</sup>
sheathing cable diameter	7.0 - 13.0 mm
type of conductor	fine stranded, stranded, solid
stripping length	6.0 mm
dismantling length	25.0 mm
clamping units per pole	1
grommet assembly	2.0 Nm
contact screw assembly	M3 - max. $\curvearrowright$ 0.8 Nm
pole marking	1-2-3
strain relief assembly	$\curvearrowright$ 2.5 Nm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>max</sub> component (operation)	125 °C
T <sub>min</sub> component (operation)	-40 °C
IP Code acc. to EN 60529	IP68/IP69

## Materials

<b>insulator material</b>	PA
<b>contact material</b>	brass
<b>flammability rating acc. to UL 94</b>	V-0

## Approvals

<b>acc. to EN 60998</b>	yes
-------------------------	-----

## Accessories

<b>AC 179 RVK/ 4 M20</b>	749564
<b>AC 173 BC SW</b>	26280
<b>DR 16 1x14,0</b>	729031
<b>DR 16 1x4,0</b>	729033
<b>DR 16 1x6,5</b>	729034
<b>DR 16 2x4,0</b>	729035
<b>DR 16 2x5,5</b>	729036
<b>DR 16 3x4,0</b>	729037
<b>DR 16 4x3,5</b>	729038
<b>DR 16 5x3,5</b>	729009
<b>DR 16 RH</b>	729011
<b>DR 16 GS</b>	729032