



SMD Connectors

SMDblank/ 1



Order Info

| | |
|-----------------------------|----------------------|
| reference number (ref. no.) | 351901 |
| PU | 2,800 (tape-on-reel) |
| EAN | 4028012123865 |

Type

| | |
|-----------------|----------------|
| Type | Terminal Block |
| connection type | push-in |
| number of poles | 1 pole |

Electrical Data

| | |
|---------------|-------|
| rated voltage | 320 V |
| rated current | 4 A |

Connection Data

| | |
|-----------------------------|------------------------------------|
| cross-section rating (UL) | 24-20 AWG |
| clamping range | hor 0.2 / vert 0.5 mm ² |
| type of conductor | fine stranded, stranded, solid |
| stripping length horizontal | 3.0 mm |
| stripping length verticl | 8.0 - 9.0 mm |
| clamping units per pole | 1 |

Ambient Conditions

| | |
|---|--------|
| T _{max} ambient air (at rated current) | 85 °C |
| T _{max} component (operation) | 105 °C |
| T _{min} component (operation) | -40 °C |

Materials

| | |
|------------------|----------------------|
| contact material | spring steel, copper |
|------------------|----------------------|

Accessories

| | |
|--------------|--------|
| SMDblank WKZ | 351999 |
|--------------|--------|