



Lighting and Housing Connection IP66

LCS 75/ 3-2

Order Info

reference number (ref. no.)	526232
PU	500
EAN	4028012134045



Type

Type	panel mount terminal block
connection type	push-in
number of poles	2 pole
colour	grey

Electrical Data

rated voltage	250 V
rated current	16 A
rated impulse voltage	2.0 kV

Connection Data

cross-section rating	2.5 mm ²
clamping range	0.5 - 2.5 mm ²
sheathing cable diameter	7.5 - 12.5 mm
type of conductor internal	solid
type of conductor external	fine stranded, stranded, solid
stripping length internal	12.0 mm
stripping length external	17.0 mm
dismantling length	60.0 mm
clamping units per pole	external: 1 / internal: 2
lock nut assembly	0.7 Nm
grommet assembly	0.7 Nm
housing hole	M20
pole marking	L N
wall thickness	0.5 - 2.5 mm

Ambient Conditions

T _{max} ambient air (at rated current)	40 °C
T _{max} component (operation)	70 °C
IP Code acc. to EN 60529	IP66

ammonia resistance	yes
---------------------------	-----

Materials

insulator material	PA
---------------------------	----

gasket material	TPS
------------------------	-----

contact material	spring steel, copper
-------------------------	----------------------

Approvals

acc. to EN 60998	yes
-------------------------	-----

Accessories

ABK 75/ 3	526204
------------------	--------